



F-500 EA[®] QAMU

Powered by
HCT's Fluorine-Free
Encapsulator Technology

Engineered Advantage

The F-500 EA[®] QAMU provides all terrain incipient fire protection at a higher capacity in an industrial environment. This is an excellent tool enabling fire brigades to respond to emergencies instantly and appropriately, targeting the source of a fire to prevent spread.



Nominal Measurements

Capacity	25-100 L (6-26 G)
Weight	32- 57 KGS (70-125 LBS)
Time	45-195 SEC
Distance	16-20 M (55-65 FT)
Working Pressure	10 BAR (150 PSI)

APPLICATIONS

Class A Hazards
Common Materials

Class B Hazards
Flammable Liquids

Class D Hazards
Combustible Metals

Class K Hazards
Oils and Fats

Lithium-ion Hazards
EVs, Handling Equipment, Etc.

Firefighting



Fire Protection



**Find the Right
Unit for Your Team**

Part #	Capacity	Weight	Time	Distance
QAMU-F500-025L	25 L (6 G)	32 KGS (70 LBS)	45 SEC	16-18 M (55-60 FT)
QAMU-F500-050L	50 L (13 G)	40 KGS (87 LBS)	90 SEC	18-20 M (60-65 FT)
QAMU-F500-075L	75 L (20 G)	42.5 KGS (94 LBS)	195 SEC	16-18 M (55-60 FT)
QAMU-F500-100L	100 L (26 G)	57 KGS (125 LBS)	195 SEC	16-18 M (55-60 FT)